

SGT Docking Station



DESCRIPTION

Using SGT Docking station lets safety managers maintain large number of devices easily. A Bump test and calibrating devices are the key features to ensure the safety of devices and users. SGT docking station version II fulfills auto calibrating/bump test function by pressing buttons simply. Long-lasting battery life and enough capacity for event logs are one of the noticeable features of Docking Station. With these features, it is possible Safety Managers can maintain all the important event logs that demonstrate users are working within company requirements.

KEY FEATURE

- Calibration, bump test
- Display status on power LED and unit LED
- Save the status and results of Docking Station and SGT
- Upgrade Docking Station and SGT firmware
- Save the log data of Docking Station and SGT
- Support user options using a PC program (IR Link/USB)

SPECIFICATION

Model	SGT Docking Station
Dimension	47 (W) x 41 (H) x 22 (D)cm (18.50 x 16.14 x 8.66 in)
Weight	8.2kg (Without Gas Cylinder)
Operation Temperature	41°F~104°F (5°C~40°C)
Warranty	Full 2 years
Battery Type	Rechargeable Lithium Ion
Battery Life	1,000 Bump Tests
LEDs	5 red/green/orange LEDs (1 for each unit, 1 for power)
Memory	USB 8GB Standard
Log Capacity	Approximately Up to 10 million tests (8GB, Removable USB memory)
Tests Performed	Bump Test and Calibration
Information Stored	Bump/Cal Logs, Individual monitor Event Logs, Firmware and Unit Configurations
Gases Available	O2, CO, and H2S
Unit Compatibility	Works with SGT/SGT-P O2, CO, H2S
Calibration Gas	Compatible with 58L cylinders
Charging Adaptor	12V, 3A
Certification	EMC, WEEE, RoHS2, REACH, RCM(ACMA&RSM), FCC

